

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) ~~Method~~ A method for managing dynamic context comprising:

storing associations between at least one activity ~~stream~~, stream and at least one representation element;

synthesizing a value of a human sensible attribute of at the least one representation element based on changes in the at least one activity stream and the stored associations;

determining a user's focus of attention; and

selecting at least one of the at least one representation elements to synthesize a display attribute based on the user's focus of attention, wherein the at least one selected representation element is within the user's focus of attention.
2. (Canceled)
3. (Currently Amended) The method of claim 1 ~~claim 2~~, wherein the selected representation element is at the periphery of the ~~user~~ user's focus of attention.
4. (Currently Amended) The method of claim 1, wherein an activity stream is information ~~from~~ including at least one of sensor information, detector information, application information, telephone information, news ~~information~~ information, and pager information.
5. (Original) The method of claim 1, wherein the human-sensible attribute is synthesized based on a selected range.
6. (Original) The method of claim 1, wherein the human-sensible attribute is synthesized based on values outside a selected range.

7. (Currently Amended) The method of claim 1, ~~where selecting~~wherein the at least one activity stream ~~comprises dynamically selecting the at least one activity stream based on which of the at least one activity stream~~ has a value outside a predicted range of values.

8. (Original) The method of claim 7, further comprising determining the predicted range of values based on monitoring at least one of the at least one activity stream.

9. (Original) The method of claim 1, wherein the human-sensible attribute is a display attribute.

10. (Original) The method of claim 9, wherein the display attribute includes at least one of a text characteristic, a window characteristic, a desktop characteristic.

11. (Currently Amended) ~~The~~ A system for managing dynamic context, comprising:

at least one synthesizer circuit, each synthesizer circuit synthesizing at least one human-sensible attribute of at least one representation element based on changes in at least one activity ~~stream-stream~~;

a memory that stores associations between the at least one activity stream, the at least one representation ~~element~~ and the synthesizer circuit; and

a user focus of attention determining circuit that determines a user's focus of attention, wherein the at least one representation element is within the user's focus of attention.

12. (Canceled)

13. (Currently Amended) The system of claim 11, wherein the at least one of the at least one activity stream is an input signal ~~from~~ including at least one of a sensor signal, a detector signal, an application signal, a telephone signal, a news ~~signal-signal~~, and a pager signal.

14. (Original) The system of claim 11, wherein at least one of the at least one synthesizer circuits synthesizes the human-sensible attributes based on a selected range.

15. (Original) The system of claim 11, wherein at least one of the at least one synthesizer circuits synthesizes the human-sensible attributes based on activity stream values outside a selected range.

16. (Original) The system of claim 11, wherein the at least one representation element and the at least one activity stream are dynamically associated based on which of the at least one activity stream has a value outside a predicted range of values.

17. (Original) The system of claim 16, wherein the predicted range of values is determined by monitoring at least one of the at least one activity stream.

18. (Original) The system of claim 11, wherein the human-sensible attribute is a display attribute.

19. (Currently Amended) The system of claim 18, wherein the display attribute includes at least one of a text characteristic, a window characteristic, and a desktop characteristic.

20. (New) The method of claim 1, wherein determining a user's focus of attention comprises determining a users focus of attention by actively sensing the user's focus of attention.

21. (New) A method for managing dynamic context comprising:
storing associations between at least one activity stream, other than a presence or lack of new information on a floating window, and at least one representation element, other than a visual translucency of the floating window; and
synthesizing a value of a human sensible attribute of at the least one representation element based on changes in the at least one activity stream and the stored associations.